

35.8 × 50.0mm PMDC Motors

- Typical Applications:
 - Precision Instruments
 - Office Automation Equipments
 - Automotive Products



● **Motor Specifications (马达特性)**

MODEL 型号	Voltage		No Load		At Maximum Efficiency					Stall		Brush Type	Length	
	Range	Nominal	Speed	Current	Speed	Current	Torque	Output	Torque	Current				
	Vdc	Vdc	r / min	A	r / min	A	g*cmN*m	W	g*cmN*m	A	M/C	mm		
JD-RS540SH-16400	12~32	24V	3752	0.058	3330	0.47	106	10.4	3.8	946	92.7	3.74	Carbon	50
JD-RS540SH-24210	4.5~12	12V	3607	0.124	2993	0.614	146	14.3	4.69	861	84.4	3.0	Carbon	50
JD-RS540SH-5045	4.5~12	12V	17500	0.95	15100	5.93	325	31.9	50.3	2350	230	37.0	Carbon	50
JD-RS540SH-7520	3.6~7.2	4.8V	15400	2.00	13000	10.90	264	25.9	35.2	1700	167	59.0	Carbon	50
JD-RS540-4070	5-15	6.0V	7600	0.46	6226	2.1	120	11.8	7.7	665	65.2		Carbon	50
JD-RS540-7516	2.4-4.5	3.6V	1900	2.8	16000	11	120	11.8	19.7	820	80.4	58.8	Carbon	50
JD-RS540S-25150	3-15	12.0V	5530	0.22	4650	0.96	140	13.7	6.68	880	86.3		Carbon	50
JD-RS540S-5045	4.5-15	6.0V	8400	0.62	7200	3.91	219	21.5	16.2	1600	157	24.7	Carbon	50
JD-RS540S-6530	3-9	7.2V	16000	1.12	13930	2.26	260	25.5	34.3	1855	182		Carbon	50
JD-RS540S-7520	3.6-7.2	4.8V	14800	1.5	12900	8.2	220	21.6	29.1	1860	182		Carbon	50
JD-RS540S-8015	3-6	4.8V	18500	2	15600	10.8	206	20.2	33.1	1320	129		Carbon	50
JD-RS540M-5045	3-12	6.0V	11370	0.078	9525	3.84	160	15.7	15.6	986	96.7	19.6	Carbon	50
JD-RS540SM-10009	9-24	3.6V	22560	3.33	16560	12.5	200	19.6	33.9	754	73.9		Carbon	50
JD-RS540SM-5045	9-24	12.0V	16600	0.7	14370	4.59	290	28.4	42.7	2160	212		Carbon	50
JD-RS540SM-6035	4.5-15	12.0V	22400	1.3	19100	6	300	29.4	58.7	2036	200		Carbon	50
JD-RS540SM-6530	3.6-7.2	7.2V	16000	1.17	12100	10.3	300	29.4	37.2	2190	215		Carbon	50
JD-RS540SM-7030	6-12	12.0V	26100	1.6	22075	7.59	350	34.3	79.2	2269	222	41	Carbon	50
JD-RS540SM-7522	3-9	6.0V	16500	1.7	14300	5.56	200	19.6	29.3	1500	147		Carbon	50
JD-RS545SH-5018	4.5~12	12V	24000	1.30	20510	7.65	317	31.1	66.7	2180	214	45.0	Carbon	50
JD-RS545SH-18150	12~32	24V	5600	0.12	4560	0.53	167	16.4	7.82	900	88.2	2.30	Carbon	50
JD-RS545SH-22100	12~24	12V	4200	0.16	3350	0.63	127	12.5	4.36	630	61.7	2.50	Carbon	50
JD-RS545-2485	12-32	24.0V	14800	0.21	12728	1.34	140	13.7	1803	1000	98		Carbon	50
JD-RS545-4519	3-12	8.0V	22600	1.2	18850	5.95	190	18.6	37	1145	112		Carbon	50
JD-RS545S-22100	12-24	12.0V	4200	0.16	3500	0.55	100	9.81	3.6	620	60.8		Carbon	50
JD-RS545S-2485	12-30	12.0V	5150	0.2	4210	0.89	146	14.3	6.3	800	78.4		Carbon	50
JD-RS545S-4045	6-18	12.0V	10000	0.5	8360	2.55	229	22.5	19.6	1395	137	13	Carbon	50
JD-RS545S-5016	3-12	7.2V	16200	1.2	13600	6.3	195	19.1	22.7	1215	119		Carbon	50

地址：浙江省余姚市经济开发区 B 区横三路。TEL: 0574-62820655/62831828, FAX: 0574-62823099

E-mail: jundi@mail.nbptt.zj.cn / jundi@vip.163.com 网址: <http://www.jdmotor.com>

● Motor Dimensions (外形尺寸图)

